



FORCE 165 230V ACX PLASTIC CARRY CASE



Overview

FORCE 165 230V ACX PLASTIC CARRY CASE

cod. 815857

MMA inverter, electrode welding machine in direct current (DC).

Usable electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Reduced weight and dimensions
- High welding current stability in spite of mains voltage fluctuations
- Arc force, hot start and anti-stick devices
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator ($\pm 15\%$) protections.

Complete with MMA welding accessories and plastic carry case.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data



CODE 815857



MAX ABSORBED CURRENT 31 A



SINGLE PHASE MAINS VOLTAGE 230 V



MAX ABSORBED POWER 4,1 kW



PROTECTION DEGREE IP21



MAINS FREQUENCY 50 / 60 Hz



MOTORGENERATOR MINIMUM POWER
6 kW



DIMENSIONS 38 x 42 x 17 cm



CURRENT RANGE 10 - 150 A



MAINS FUSE 16 A



WEIGHT 5,5 kg



%USE (20°C USE) 60% @ 150A %



EFFICIENCY 82 V



EAN CODE 800489778955 2



MAX CURRENT DC (EN 60974-1) 140 @
7% A



POWER FACTOR (cosphi) 0,6



PIECES/PALLET 36 pz/pallet



MAX NO LOAD VOLTAGE 72 V



D. USABLE ELECTRODES IN DC 1,6 - 4
mm




FORCE 165 230V ACX PLASTIC CARRY CASE

Included Accessories

 CABLE 16 MMQ 1,8 M - PLUG ATLAS 25 - 124508



 TOLEDO 250 WORK CLAMP 250A - 712030



SLAG REMOVER - 712139



DALLAS 300 ELECTRODE HOLDER 300A - 712260