



## ELECTROMIG 300 SYNERGIC 400V



### Overview

#### ELECTROMIG 300 SYNERGIC 400V

cod. 816065

MIG-MAG/FLUX/BRAZING/MMA and TIG DC-Lift multiprocess inverter welding machine controlled by a microprocessor, with 4-roller wire feeder.

Flexible use with various welded materials (steel, stainless steel, aluminium) or brazed materials (galvanised sheet metal). Wide variety of application fields, from industry to maintenance, installation to bodywork activities.

Synergic adjustment makes the product simple to use.

The Made in Telwin ATC technology makes it easy to achieve excellent standards of welding on thin materials thanks to state-of-the-art control of the arc.

#### Features:

- Manual or synergic operating;
- 30 pre-set synergic curves;
- MIG-MAG adjustments: wire up slope, electronic reactance, wire burn-back time, post gas;
- 2/4 time operation selection, spot, inch and mm material thicknesses;
- Protections: thermostatic, overvoltage, undervoltage, overcurrent, engine driven generator (+/-15%);
- TIG Lift












Complete with MIG-MAG torch, cable and earth clamp.

### Technical data

<b>CODE</b>	CODE 816065	<b>A<sub>MAX</sub></b>	MAX ABSORBED CURRENT 15 A	<b>Ø<sub>DC</sub> MIN/MAX</b>	D. USABLE ELECTRODES IN DC 1,6 - 6 mm
<b>V<sub>3PH</sub></b>	THREE PHASE MAINS VOLTAGE 400 V	<b>A<sub>60% MAX</sub></b>	ABSORBED CURRENT AT 60% - MAX 10 A	<b>Ø<sub>ST</sub></b>	STEEL WELDING WIRE DIAMETER 0,6 - 1,2 mm
<b>F</b>	MAINS FREQUENCY 50 / 60 Hz	<b>P<sub>MAX</sub></b>	MAX ABSORBED POWER 9 kW	<b>Ø<sub>SS</sub></b>	INOX WELDING WIRE DIAMETER 0,8 - 1,2 mm



## ELECTROMIG 300 SYNERGIC 400V

 CURRENT RANGE 20 - 300 A	 ABSORBED POWER AT 60% 6,5 kW	 ALUMINIUM WELDING WIRE DIAM. 0,8 - 1,2 mm
 MAX CURRENT 270 A - 30%	 MAINS FUSE 16 A	 FLUX CORED WELDING WIRE DIAM. 0,8 - 1,2 mm
 CURRENT AT 60% 205 A	 EFFICIENCY 90 %	 BRAZING WIRE DIAM. 0,8 - 1,2 mm
 MAX NO LOAD VOLTAGE 63 V	 POWER FACTOR (cosphi) 0,9	

### Included Accessories

 MT25 MIG TORCH 3 M - 742183