



TECNICA 211/S 230V ACX PLASTIC C.CASE



Overview

TECNICA 211/S 230V ACX PLASTIC C.CASE

cod. 816122

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- compact and light
 - high welding current stability in spite of mains voltage fluctuations
 - arc force, hot start and anti-stick devices
 - thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.
- Complete with MMA welding accessories and plastic carry case.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 816122	DC CURRENT	105 A		MAINS FUSE 16 A
SINGLE PHASE MAINS VOLTAGE	230 V	MAX NO LOAD VOLTAGE	75 V		EFFICIENCY 88 %
MAINS FREQUENCY	50 / 60 Hz	MAX ABSORBED CURRENT	34 A		POWER FACTOR (cosphi) 0,7
CURRENT RANGE	15 - 180 A	ABSORBED CURRENT AT 60% - MAX	19 A		D. USABLE ELECTRODES IN DC 1,6 - 4 mm
%USE (20°C USE)	65% @ 180A %	MAX ABSORBED POWER	5,3 kW	MAX CURRENT DC (EN 60974-1)	170 @ 18 % A
ABSORBED POWER AT 60%	2,9 kW	PROTECTION DEGREE	IP23	MOTORGENERATOR MINIMUM POWER	7 kW

Included Accessories



TECNICA 211/S 230V ACX PLASTIC C.CASE

CABLE TW05V-A 1X025 1.80M PLUG ATLAS - 124589

PLASTIC CARRY CASE - 322800



TOLEDO 250 WORK CLAMP 250A - 712030



DALLAS 300 ELECTRODE HOLDER 300A - 712260