



SUPERIOR TIG 421 DC-HF/LIFT 400V AQUA



Overview

SUPERIOR TIG 421 DC-HF/LIFT 400V AQUA

cod. 816133

Microprocessor controlled, TIG (high frequency HF or LIFT striking), PULSE TIG and MMA inverter welding machine in direct current (DC).

Use with a wide range of materials such as steel, stainless steel, titanium, copper, nickel and their alloys.

Features:

- pulse and EASY pulse operation,
- 9 customized welding programs,
- TIG regulations: bi-level, start up/end current, spot welding time, pre/post gas, current up/down slope, balance DC, square wave frequency,
- MMA regulations: arc force and hot start according to the type of electrode in use,
- anti-stick device,
- remote control and G.R.A. water cooling connector,
- storage on on-board E2PROM of the last 10 alarms,
- thermostatic, overvoltage, undervoltage, inside dirtiness, overcurrent, phase failure, water cooling unit protections.

Complete with TIG welding accessories, trolley and water cooling unit G.R.A..



REMOTE CONTROLS



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 816133	V_{0 DC}	MAX NO LOAD VOLTAGE 64 V	Φ	POWER FACTOR (cosphi) 0,9
V_{3PH}	THREE PHASE MAINS VOLTAGE 400 V	A_{MAX}	MAX ABSORBED CURRENT 21 A	Ø_{DC MIN/MAX}	D. USABLE ELECTRODES IN DC 1,6 - 6 mm
F	MAINS FREQUENCY 50 / 60 Hz	A_{60% MAX}	ABSORBED CURRENT AT 60% - MAX 13 A	A_{MIN MAX DC}	CURRENT RANGE 5 - 350 A
P_{MAX}	MAX ABSORBED POWER 14 kW	IP	PROTECTION DEGREE IP23	A_{MAX 40°C DC}	MAX CURRENT DC (EN 60974-1) 350 @ 35 % A



SUPERIOR TIG 421 DC-HF/LIFT 400V AQUA



ABSORBED POWER AT 60% 8 kW



DIMENSIONS 93,5 x 50 x 119,5 cm



DC CURRENT 250 A



MAINS FUSE 16 A



WEIGHT 67 kg



EFFICIENCY 85 V

Included Accessories



ARGON GAS BOTTLE IT ADAPTOR - 432036

ST18A TIG TORCH DX50 4M AQUA - 742615



TOLEDO 300 WORK CLAMP - 712231



G.R.A. 4000 WATER COOLING UNIT 230V - 802640

CABLE 25 MMQ 3 M - DINSE 50 - 713504



TROLLEY - MONDIAL - 803072



GAS REGULATOR 2 MANOMETERS 12 L\min - 722119