

ST18A TIG TORCH AX50 4M AQUA GREEN LINE



- Professional TIG torch ST18A GREEN LINE with 4m leather cable.
- AX50 connector, 5-pin control cable, G 3/8 gas connector.
- Button control.
- Water cooling (4 bar pressure, 1.5 l/min flow).
- Remote control integrated with potentiometer.
- Max current 320A DC / 225A AC @35%.

TECHNICAL DATA

CODE	742617	T04055	AX50	T04053	Potentiometer 1KOhm
COOLING	LIQUID	T04056	G 3/8	STANDARD	EN 60974-7
CABLE LENGTH	4 m	T04057	5 pin	DIMENSIONS	590x390x75 mm
T04050	8 mm ²	T04051	4 bar	WEIGHT	2,830 kg
MAX CURRENT	320ADC/225AAC@100%A	T04052	1.5		

OPTIONAL ACCESSORIES

TIG CONSUMABLES BOXES

804138	CONSUMABLES BOX FOR TIG TORCH ST17-26
--------	---------------------------------------

TIG CONSUMABLES

802222	KIT 10 CERIUM-TUNGSTEN ELECTR. D.1,6 MM
802232	KIT 10 CERIUM-TUNGSTEN ELECTR. D.2,4 MM
802233	KIT 10 CERIUM-TUNGSTEN ELECTR. D.3,2 MM
802235	KIT 10 PURE TUNGSTEN ELECTR. D.1,6 MM
802236	KIT 10 PURE TUNGSTEN ELECTR. D.2,4 MM
802237	KIT 10 PURE TUNGSTEN ELECTR. D.3,2 MM
802238	KIT 10 PURE TUNGSTEN ELECTR. D. 4 MM
802250	ELECTRODE DIFFUSERS Ø 1,6 MM 3 PCS
802251	ELECTRODE DIFFUSERS Ø 2,4 MM 3 PCS
802252	ELECTRODE DIFFUSERS Ø 3,2 MM 3 PCS
802253	ELECTRODE DIFFUSERS Ø 4 MM 3 PCS
802240	KIT 3 ELECTRODE HOLDER CLAMPS D.1,6 MM
802241	KIT 3 ELECTRODE HOLDER CLAMPS D.2,4 MM
802242	KIT 3 ELECTRODE HOLDER CLAMPS D.3,2 MM
802243	KIT 3 ELECTRODE HOLDER CLAMPS D.4 MM
802245	KIT 10 CERAMIC NOZZLES NR.6
802246	KIT 10 CERAMIC NOZZLES NR.7
802247	KIT 10 CERAMIC NOZZLES NR.8
802248	KIT 10 CERAMIC NOZZLES NR.10
722192	SHORT CAP ST17-26
722193	LONG CAP

SPECIAL TIG CONSUMABLES

804202	CRYSTAL CHAMPAGNE BOX D. 1,6 MM
804206	CRYSTAL CLEAR CUP - LONG - BOX D. 1,6 MM
804203	CRYSTAL CHAMPAGNE BOX D. 2,4 MM
804207	CRYSTAL CLEAR CUP - LONG - BOX D. 2,4 MM
804205	CRYSTAL CLEAR CUP - BOX D. 2,4 MM
804204	CRYSTAL CLEAR CUP - BOX D. 1,6 MM

BLISTER ACCESSORIES

804127	TIG TORCH MAGNETIC HOLDER
--------	---------------------------

DESCRIPTION

Professional, high efficiency and ergonomic torch for TIG welding ST18A GREEN LINE with water cooling. The 4-metre leather cable guarantees high flexibility. 5-pin control connector. The torch is equipped with a remote control potentiometer and button for gas adjustment. Suitable for works with maximum current 320A DC and 225A AC



(@35%). Gas connector type G 3/8. With 2.4 mm DC electrode and relevant consumables.

DOWNLOAD



CATALOG IMAGE