



- Battery charger for WET 12/24V batteries. With ammeter and normal or fast (BOOST) charge selector. 300W.
- Protection against overcharging and pole inversion.

## TECHNICAL DATA

CODE	<b>807546</b>	CHARGING VOLTAGE	<b>12 / 24 V</b>	MAX.RATED REFERENCE CAPAC.	<b>225 / 180 Ah</b>
SINGLEPHASE MAINS VOLTAGE	<b>230 V</b>	EFFICIENT CHARGING CURRENT	<b>18 / 12 A</b>	ADJUSTMENT POSITIONS	<b>2</b>
MAINS FREQUENCY	<b>50 / 60 Hz</b>	RATED CHAR.CUR.EN60335-2-29	<b>12 / 8 A</b>	DIMENSIONS (LxWxH)	<b>22,5 x 29 x 20,5 cm</b>
CHARGING ABSORBED POWER	<b>300 W</b>	MIN.RATED REFERENCE CAPAC.	<b>30 / 20 Ah</b>	WEIGHT	<b>6,9 kg</b>

## SUPPLIED ACCESSORIES

123985	WORK CABLE 2,5 MMQ 1,5 M
123986	POSITIVE CABLE 2,5 MMQ 1,5 M
712623	COLORADO 40R POSITIVE CLAMP 40A
712624	COLORADO 40B WORK CLAMP 40A

## OPTIONAL ACCESSORIES

<b>BATTERY CHARGERS FUSES</b>	
802257	FUSES 20A 10 PCS

## DESCRIPTION

Battery charger for charging free electrolyte batteries (WET) with 12V/24V voltage. Protected against overloads and polarity reversal. Equipped with selector for normal or quick (BOOST) charge. Equipped with ammeter.

## DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE