



- Battery charger and starter: WET/START/STOP battery charger and cranking of any type of 12/24V petrol and diesel engine up to 70 hp.
- Normal charge, fast (BOOST) charge, rapid cranking selection.
- Display of charging and cranking current.
- Protection against overcharging and pole inversion.

TECHNICAL DATA

CODE	807551	CHARGE AND STARTING VOLTAG.	12 / 24 V	MIN.RATED REFERENCE CAPAC.	20 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFICIENT CHARGING CURRENT	45 A	MAX.RATED REFERENCE CAPAC.	700 Ah
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	31 A	ADJUSTMENT POSITIONS	3
CHARGING ABSORBED POWER	1 kW	START CUR.1V/C EN60335-2-29	180 A	DIMENSIONS (LxWxH)	26,5 x 34,5 x 23 cm
STARTING ABSORBED POWER	6,4 kW	MAX STARTING CURRENT	300 A	WEIGHT	10,9 kg

SUPPLIED ACCESSORIES

123425	CABLE 10 MMQ 2 M
712001	COLORADO 150B WORK CLAMP 150A
712002	COLORADO 150R POSITIVE CLAMP 150A
120825	CABLE TW05V-F 1X010 L=02.00M-EYELET

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES	
802259	FUSES 50A 20 PCS

DESCRIPTION

Battery charger and starter for charging free electrolyte batteries (WET) with 12V/24V voltage, and starting all types of petrol-driven and diesel-driven vehicles, up to 70 hp.

Features:

- choice of normal charge, quick charge (BOOST), quick start
- display of charging and starting current
- protection against overloads and polarity reversal.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST