



- Battery charger with TRONIC technology for WET, GEL, Pb-Ca, AGM, MF, EFB 6/12 V batteries.
- Battery charge status LED signal. Key to set the voltage (12 and 24 V).
- Protection against overcharging, pole inversion and recognition of charge voltage.
- Light and compact: only 1.4 kg.

TECHNICAL DATA

CODE	807591	CHARGING VOLTAGE	6 / 12 V	MAX.RATED REFERENCE CAPAC.	30 / 55 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFICIENT CHARGING CURRENT	2 / 6 A	DIMENSIONS (LxWxH)	10 x 19 x 19 cm
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	1,5 / 3 A	WEIGHT	1,672 kg
CHARGING ABSORBED POWER	60 W	MIN.RATED REFERENCE CAPAC.	15 / 25 Ah		

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES

802859 FUSES 5A 10 PCS

DESCRIPTION

Battery charger with electronic control of the charging steps, automatic interruption and restart (TRONIC), for charging WET, GEL, Pb-Ca, AGM, MF, EFB batteries with 6V/12V voltage.

With warning LED to indicate battery charge status.

Fit with protection against overloads and polarity reversal and recognition of battery voltage.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



CERTIFICATE

USEFUL LINKS



VIDEO