



- Battery charger with TRONIC technology for WET, GEL, Pb-Ca, AGM, MF, EFB 12/24 V batteries.
- Battery charge status LED signal. Key to set the voltage (12 and 24 V).
- Protection against overcharging, pole inversion and recognition of charge voltage.
- Light and compact: only 2.9 kg.

TECHNICAL DATA

CODE	807592	CHARGING VOLTAGE	12 / 24 V	MAX.RATED REFERENCE CAPAC.	115 / 55 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFICIENT CHARGING CURRENT	12 / 6,5 A	DIMENSIONS (LxWxH)	10 x 19 x 19 cm
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	6 / 4,5 A	WEIGHT	2,930 kg
CHARGING ABSORBED POWER	130 W	MIN.RATED REFERENCE CAPAC.	50 / 30 Ah		

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES

802255 FUSES 10A 10 PCS

DESCRIPTION

Battery charger with electronic control of the charging steps, automatic interruption and restart (TRONIC), for charging WET, GEL, Pb-Ca, AGM, MF, EFB batteries with 12V/24V voltage.

With warning LED to indicate battery charge status.

Fit with protection against overloads and polarity reversal and recognition of battery voltage.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL

USEFUL LINKS



VIDEO