



**ELEMENTS** *Tronic*

12V

24V

Wet

Gel

MF

AGM

Pb-Ca

EFB



- Battery charger with TRONIC technology for WET, GEL, Pb-Ca, AGM, MF, EFB 12/24 V batteries.
- Battery charge status LED signal. Key to set the voltage (12 and 24 V).
- Protection against overcharging, pole inversion and recognition of charge voltage.
- Light and compact: only 3.4 kg.

## TECHNICAL DATA

CODE	<b>807593</b>	CHARGING VOLTAGE	<b>12 / 24 V</b>	MAX.RATED REFERENCE CAPAC.	<b>180 / 115 Ah</b>
SINGLEPHASE MAINS VOLTAGE	<b>230 V</b>	EFFICIENT CHARGING CURRENT	<b>15 / 8 A</b>	DIMENSIONS (LxWxH)	<b>10 x 19 x 19 cm</b>
MAINS FREQUENCY	<b>50 / 60 Hz</b>	RATED CHAR.CUR.EN60335-2-29	<b>9 / 6 A</b>	WEIGHT	<b>3,440 kg</b>
CHARGING ABSORBED POWER	<b>230 W</b>	MIN.RATED REFERENCE CAPAC.	<b>60 / 50 Ah</b>		

## OPTIONAL ACCESSORIES

### BATTERY CHARGERS FUSES

802256 FUSES 15A 10 PCS

## DESCRIPTION

Battery charger with electronic control of the charging steps, automatic interruption and restart (TRONIC), for charging WET, GEL, Pb-Ca, AGM, MF, EFB batteries with 12V/24V voltage.

With warning LED to indicate battery charge status.

Fit with protection against overloads and polarity reversal and recognition of battery voltage.

## DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



CERTIFICATE

## USEFUL LINKS



VIDEO