



- Alternating current (AC) MMA electrode welding machine, 250A. Three-phase, 400V power supply. On wheels.
- Usable electrodes: rutile up to 5 mm.
- Continuous adjustment of welding current.
- Thermostatic protection.

TECHNICAL DATA

CODE	812011	AC CURRENT AT 60%	70 A	INSULATION CLASS	H
SINGLEPHASE MAINS VOLTAGE	230 V	MAX NO LOAD VOLTAGE IN AC	55 V	PROTECTION DEGREE	IP21
TWO-PHASE MAINS VOLTAGE	400 V	MAX ABSORBED POWER	8,5 kW	DIMENSIONS (LxWxH)	75 x 36 x 49 cm
MAINS FREQUENCY	50 / 60 Hz	ABSORBED POWER AT 60%	2,6 kW	WEIGHT	25 kg
CURRENT CONTROL RANGE AC	70 - 250 A	POWER FACTOR(cosphi) (cosphi)	0,55		
MAX CURRENT AC EN60974-1	200 @ 10 % A	D.USABLE ELECTRODES AC	2 - 5 mm		

OPTIONAL ACCESSORIES

ACCESSORIES/VARIOUS/SPARE PART

801096 MMA WELDING KIT 200A 16 MMQ 3+2M AX25

DESCRIPTION

MMA stick electrode welding machine in alternating current (AC).
Stepless regulation of welding current.
With thermostatic protection.
Use with a wide range of electrodes: rutile.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE