



- Direct current (DC) MMA electrode inverter welding machine, 400A, with digital display. Dual voltage.
- Arc-force adjustment and hot start according to the type of electrode used. Anti-stick protection.
- Usable electrodes: rutile, basic, stainless steel, cast iron, etc. up to 6 mm. With set welding current display.
- High stability of the welding current in power supply voltage variations.
- Resistant to dirt and dust thanks to the ventilation system (dedicated tunnel) that preserves the electronic components, guaranteeing longer duration over time.
- Strong, resistant to impact and dust; reduced weight and size.
- Contained consumption thanks to inverter technology. Set up for gouging.

## TECHNICAL DATA

CODE	<b>816182</b>	MAX ABSORBED CURRENT	<b>35 / 30 A</b>	D.USABLE ELECTRODES IN DC	<b>1,6 - 6 mm</b>
THREEPHASE MAINS VOLTAGE	<b>230 / 400 V</b>	ABSORBED CURRENT AT 60%	<b>25 / 20 A</b>	INSULATION CLASS	<b>F</b>
MAINS FREQUENCY	<b>50 / 60 Hz</b>	MAX ABSORBED POWER	<b>11 / 16,2 kW</b>	PROTECTION DEGREE	<b>IP23</b>
CURRENT RANGE IN DC	<b>20-320/20-400A</b>	ABSORBED POWER AT 60%	<b>7,9 / 10,8 kW</b>	DIMENSIONS (LxWxH)	<b>54,6 x 27,4 x 50 cm</b>
MAX CURRENT DC EN60974-1	<b>300@40%/400@40%A</b>	MOTORGGENER. MINIMUM POWER	<b>16 / 23 kW</b>	WEIGHT	<b>21 kg</b>
DC CURRENT AT 60%	<b>240 / 300 A</b>	EFFICIENCY	<b>90 %</b>		
MAX NO LOAD VOLTAGE IN DC	<b>82 / 77 V</b>	POWER FACTOR(cosphi) (cosphi)	<b>0,77</b>		

## OPTIONAL ACCESSORIES

### GOUGING ACCESSORIES

802666	GOUGING KIT
802803	CARBON ELECTRODES D. 8 300 MM 5 PCS
802305	CARBON ELECTRODES D. 10 300 MM 5 PCS

### OTHER ACCESSORIES

804318	WHEELS KIT LINEAR i /SUPERMIG i
--------	---------------------------------

### TROLLEYS AND ACCESSORIES

803064	TROLLEY - CONTINENTAL
--------	-----------------------

### ACCESSORIES/VARIOUS/SPARE PART

801093	MMA WELDING KIT 400A 50 MMQ 4+3M AX50
--------	---------------------------------------

## DESCRIPTION

Inverter MMA electrode welding machine in direct current (DC).

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron.

Ideal for use with motor generators, it maintains a high level of stability of the welding current to variations in the supply voltage, both to undervoltage (-25%) and overvoltage (+15%).

Particularly resistant to dirt and dust thanks to the special construction of the ventilation system which, following a dedicated tunnel, preserves the electronic components, guaranteeing a longer life.

Features:

- Robust, impact resistant and dustproof;
- Low weight and size;
- High energy saving;
- Display to show pre-set welding current;
- High stability of the welding current despite variations in the supply voltage;
- Synergic adjustment of Arc Frce and Hot Start according to the type of electrode in use;
- Anti-stick device;
- Thermostat, undervoltage (-25%), overvoltage (+15%), overcurrent, motor-generator protections.

**DOWNLOAD**

---



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



BROCHURE



CERTIFICATE