



- TIG AC/DC (HF or LIFT), TIG PULSE (PULSE and EASY PULSE) and MMA inverter welding machine, 200A.
- With LCD display for interaction and simplified adjustment of the welding parameters.
- PULSE and EASY PULSE operation. THINSPOT advanced utility for easy, rapid and accurate TIG spot welding of thin sheet metal. MIX AC-DC to heat the workpiece to weld and prepare it for AC welding.
- 10 customisable welding programs.
- MMA welding: continuous or pulse mode (MMA Pulse).
- Resistant to dirt and dust thanks to the ventilation system (dedicated tunnel) that preserves the electronic components, guaranteeing longer duration over time. Solid and strong structure.
- Setup for remote controls.

TECHNICAL DATA

CODE	816208	MAX NO LOAD VOLTAGE IN DC	66 V	POWER FACTOR(cosphi) (cosphi)	0,69
SINGLEPHASE MAINS VOLTAGE	230 V	MAX ABSORBED CURRENT	33 A	D.USABLE ELECTRODES IN DC	1,6 - 4 mm
MAINS FREQUENCY	50 / 60 Hz	ABSORBED CURRENT AT 60%	24 A	INSULATION CLASS	F
CURRENT RANGE IN DC	5 - 200 A	MAX ABSORBED POWER	5,2 kW	PROTECTION DEGREE	IP23
MAX CURRENT DC EN60974-1	200 @ 35 % A	ABSORBED POWER AT 60%	3,8 kW	DIMENSIONS (LxWxH)	47 x 19 x 35 cm
CURRENT 35% DC	200 A	MAINS FUSE	20 A	WEIGHT	11,5 kg
DC CURRENT AT 60%	125 A	EFFICIENCY	82 %		

OPTIONAL ACCESSORIES

ELECTRODE HOLDERS WITH CABLE		743029	ST26 PRO-C 4M AX50 5P TIG TORCH
804123	ELECTRODE HOLDER + CABLE 25MMQ 4M AX50	743031	ST26 PRO-C 8M AX50 5P TIG TORCH
REMOTE CONTROLS		743025	ST26 PRO-P 4M AX50 5P TIG TORCH
802336	RC-20 10 M CONTROL 2POT	743027	ST26 PRO-P 8M AX50 5P TIG TORCH
804456	FPC-200 10 M FOOT CONTROL	TIG TORCHES - PREMIUM AQUA	
GAS REGULATORS		743030	ST18A PRO-C 4M AQUA AX50 5P TIG TORCH
804208	QUICK GAS CONNECTOR	743032	ST18A PRO-C 8M AQUA AX50 5P TIG TORCH
TIG WELDING KITS		743026	ST18A PRO-P 4M AQUA AX50 5P TIG TORCH
802788	TIG WELDING KIT - ST26	743028	ST18A PRO-P 8M AQUA AX50 5P TIG TORCH
TIG TORCHES		WATER COOLING UNITS	
743121	ST26 4M AX50 5P TIG TORCH	802790	GRA 4500 WATER COOLING UNIT
743123	ST26 8M AX50 5P TIG TORCH	802976	COOLANT FOR COOLING SYSTEMS
TIG - AQUA TORCHES		TROLLEYS AND ACCESSORIES	
743044	ST20A PRO 4M AQUA AX50 5P TIG TORCH	803059	TROLLEY - ARCTIC
TIG TORCHES - PREMIUM		803084	TROLLEY - AMERICA
		803079	TROLLEY - COSMOPOLITAN

DESCRIPTION

TIG AC/DC (HF or LIFT), TIG PULSE (PULSE and EASY PULSE) and MMA inverter welding machine.

Use with different types of materials such as steel, stainless steel, aluminium, titanium, copper, nickel, magnesium and their alloys.

Designed to ensure excellent results on every thickness even the thinnest ones, the PULSE mode (also in the EASY PULSE version) reduces material deformation ensuring high arc stability.

Presence of advanced features: MIX AC-DC for preparation of AC welding of workpieces with considerable weights; THINSPOT for spot welding of very thin sheet metal.

The LCD screen facilitates interaction with the product and simplifies adjustment of multiple parameters of the TIG welding curve depending on processing needs.

You can save and retrieve customised programs.

Electrode welding both in continuous and pulsed mode (MMA Pulse) which ensures excellent results with basic electrodes and in position welding.

Designed for reliability over time, they feature a dedicated air tunnel cooling system that protects against dust and dirt.

Features:

TIG

- operation in pulse and EASY pulse mode; in 2/ 4 times, Bi Level;
- 10 customisable welding programs;
- adjustment of multiple welding curve parameters: pre-heating electrode, initial/final current, spot time, pre/post gas, start/end current ramp, DC/AC balance, square wave frequency;
- advanced functions: THINSPOT for spot welding of very thin sheet metal; MIX AC-DC to heat the workpiece to weld and prepare it for AC welding;
- optimised minimum current start-up (HF/LIFT);
- set up for remote control ;
- compatibility with PRO torches;

MMA

- direct current and pulse (MMA PULSE) operation;
- hot start, arc force settings;
- anti-stick protection;
- VRD device;

Other features:

- LCD screen for simplified interaction and immediate display and parameter setting;
- reliability over time thanks to cooling system with dedicated air tunnel that protects against dust and dirt;
- ensures the best performance even in the presence of undervoltages (up to -15%) and overvoltages (+ 15%);
- compact and robust design for easier transport and less space needed;
- thermostatic protection, overvoltage, undervoltage, overcurrent.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE