



- MIG-MAG/BRAZING, 500A wire welding machine. 3ph 230/400V power supply. With MIG-MAG welding accessories.
- High number of adjustment steps of the arc voltage. Spot welding time adjustment. Two reactance positions.
- Thermostatic protection.
- Extremely strong.
- Use of extensions (optional) possible to increase the distance between the wire feeder and generator up to 10m.

TECHNICAL DATA

CODE	827007	MAX NO LOAD VOLTAGE IN DC	55 V	ALUM. WELDING WIRE DIAM.	0,8 - 1,2 mm
THREEPHASE MAINS VOLTAGE	230 / 400 V	MAX ABSORBED POWER	25 kW	FLUX CORED WELDI.WIRE DIA.	1 - 2 mm
MAINS FREQUENCY	50 / 60 Hz	ABSORBED POWER AT 60%	10 kW	BRAZING WIRE DIAM.	0,8 - 1,2 mm
CURRENT RANGE IN DC	50 - 500 A	POWER FACTOR(cosphi) (cosphi)	0,9	INSULATION CLASS	H
MAX CURRENT DC EN60974-1	500 @ 25 % A	ADJUSTMENT POSITIONS	24	PROTECTION DEGREE	IP22
CURRENT 35% DC	370 A	STEEL WELDING WIRE DIAMET.	0,6 - 2 mm	DIMENSIONS (LxWxH)	94,5 x 56,5 x 83 cm
DC CURRENT AT 60%	280 A	INOX WELDI.WIRE DIAMETER	0,8 - 2 mm	WEIGHT	120 kg

SUPPLIED ACCESSORIES

432036	ARGON GAS BOTTLE IT ADAPTOR
644444	TORCH HOOK
722346	GAS REGULATOR 2 MANOMETERS 32 L\min
742186	MT36 MIG TORCH 3M
804125	WORK CLAMP + CABLE 50MMQ 3M AX50
742576	FEED ROLL 4R 0,6FE-0,8/0,9FE "P-K"
742366	FEED ROLL 4R 1,0FE-1,2FE "P-K"

OPTIONAL ACCESSORIES

MIG/MAG WELDING KITS		802595	COIL COVER KIT
802273	ALUMINIUM WELDING KIT D. 1-1,6 MM	802486	COIL ADAPTOR B-300
802466	FLUX CORED WIRE WELDING KIT D. 1-1,6 MM	MIG CONNECTION CABLES	
MIG TORCHES		802266	CONNECTING CABLE 50 MMQ 4M 8 POLES
742187	MT36 MIG TORCH 4M	802267	CONNECTING CABLE 50MMQ 10M 8 POLES
742188	MT36 MIG TORCH 5M	WATER COOLING UNITS	
WIRE FEEDERS AND ACCESSORIES		802043	GRA 90 WATER COOLING UNIT

DESCRIPTION

MIG-MAG/FLUX/BRAZING welding machine with removable wire feeder, fit for use in the industrial field. Flexibility of use with a wide range of materials such as steel, stainless steel, high strength steels and aluminium. Features:

- Very strong
- Numerous steps for regulation of arc voltage
- Regulation of spot welding time
- Two positions for reactance
- Thermostatic protection

Thanks to the extensions (optional) it is possible to increase the working range between wire feeder and power source up to 10 meters.

Complete with MIG-MAG welding accessories.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE