



- Battery manager for complete maintenance and rapid start of 12V/24V WET, GEL, AGM, MF, PbCa, EFB and Li batteries. 300A start max. With LCD screen.
- Automatic charge and maintenance in Pulse Tronic based on the technology of the selected battery.
- Battery test, starting and alternator; regeneration and recovery of batteries; source of stable power supply for battery changes; starting.

TECHNICAL DATA

CODE	829344	CHARGE AND STARTING VOLTAG.	12 / 24 V	MIN.RATED REFERENCE CAPAC.	10 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFICIENT CHARGING CURRENT	45 A	MAX.RATED REFERENCE CAPAC.	450 Ah
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	31 A	DIMENSIONS (LxWxH)	30,5 x 36 x 63 cm
CHARGING ABSORBED POWER	1 kW	START CUR.1V/C EN60335-2-29	180 A	WEIGHT	14,5 kg
STARTING ABSORBED POWER	6,4 kW	MAX STARTING CURRENT	300 A		

SUPPLIED ACCESSORIES

123425	CABLE 10 MMQ 2 M
712747	POSITIVE CLAMP
712748	WORK CLAMP

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES	
802259	FUSES 50A 20 PCS

DESCRIPTION

Multifunction, electronic battery charger, starter and tester (BATTERY MANAGER), for WET, GEL, AGM, MF, PbCa, EFB and Li batteries at 12V/24V.

It grants complete maintenance of the batteries and quick starting of cars, vans and light trucks.

It is an indispensable tool for stable power supply during battery changes.

Easy and intuitive to use thanks to the graphical LCD screen.

Features:

- Automatic charge and maintenance in Pulse Tronic;
- Battery, start and alternator test;
- Regeneration and recovery of batteries;
- Stable power source for battery changes (safeguard of the on-board electronics);
- Starting of all types of cars, vans, light trucks.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST