



ELEMENTS

12V

24V

Wet

EFB



230V



- Battery charger and starter: WET, START-STOP 12/24V battery charger and rapid ignition of all types of vehicles, vans, etc. (570A max).
- Normal charge, boost, rapid ignition selection.
- Display of charging and ignition current.
- Protection against overcharging and pole inversion.

TECHNICAL DATA

CODE	829392	CHARGE AND STARTING VOLTAG.	12 / 24 V	MIN.RATED REFERENCE CAPAC.	20 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFICIENT CHARGING CURRENT	105 A	MAX.RATED REFERENCE CAPAC.	1550 Ah
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	70 A	ADJUSTMENT POSITIONS	4
CHARGING ABSORBED POWER	2,2 kW	START CUR.1V/C EN60335-2-29	360 A	DIMENSIONS (LxWxH)	32 x 38 x 78 cm
STARTING ABSORBED POWER	12 kW	MAX STARTING CURRENT	570 A	WEIGHT	24 kg

SUPPLIED ACCESSORIES

712001	COLORADO 150B WORK CLAMP 150A
712002	COLORADO 150R POSITIVE CLAMP 150A

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES	
802029	FUSES 100A 20 PCS

DESCRIPTION

Battery charger and starter for charging free electrolyte batteries (WET) with 12V/24V voltage and starting all kinds of cars, vans and light trucks.

Features:

- choice of normal charge, quick charge (BOOST), quick start
- display of charging and starting current
- protection against overloads and polarity reversal.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE

USEFUL LINKS



VIDEO