



- Direct current (DC) MMA and TIG (LIFT strike) electrode inverter welding machine, 150A, with LCD display. Supplied with accessories for electrode welding and plastic case.
- Strong and raised structure against dust, water and dirt. Compact, light and easy to transport.
- With set welding current display.
- Advanced arc control devices: arc force, hot start, anti-stick. Usable electrodes: rutile, basic, stainless steel, cast iron, etc. up to 4 mm.
- Thermostatic, overvoltage, undervoltage, overcurrent protection. Compatible for use with the motor generator (230V, +/-15%). High stability of the welding current in power supply voltage variations.
- Contained consumption thanks to inverter technology.

TECHNICAL DATA

CODE	816235	MAX NO LOAD VOLTAGE IN DC	82 V	POWER FACTOR(cosphi) (cosphi)	0,7
SINGLEPHASE MAINS VOLTAGE	230 V	MAX ABSORBED CURRENT	28 A	D.USABLE ELECTRODES IN DC	1,6 - 4 mm
MAINS FREQUENCY	50 / 60 Hz	ABSORBED CURRENT AT 60%	17 A	INSULATION CLASS	F
CURRENT RANGE IN DC	10 - 150 A	MAX ABSORBED POWER	4,2 kW	PROTECTION DEGREE	IP23
%USE (20°C USE) (*)	90% @ 150A	ABSORBED POWER AT 60%	2,8 kW	DIMENSIONS (LxWxH)	38 x 42 x 17 cm
MAX CURRENT DC EN60974-1	140 @ 25 % A	MOTORGNER. MINIMUM POWER	6 kW	WEIGHT	5,71 kg
CURRENT 35% DC	125 A	MAINS FUSE	16 A		
DC CURRENT AT 60%	100 A	EFFICIENCY	86 %		

SUPPLIED ACCESSORIES

322800	PLASTIC CARRY CASE
124589	CABLE TW05V-A 1X025 1.80M PLUG ATLAS
712030	TOLEDO 250 WORK CLAMP 250A
712260	DALLAS 300 ELECTRODE HOLDER 300A

OPTIONAL ACCESSORIES

TIG WELDING KITS

801097	TIG WELDING KIT - ST9V
--------	------------------------

BLISTER ELECTRODES

804569	BASIC ELECTRODES D. 2,5 MM 10 PCS
804570	BASIC ELECTRODES D. 3,2 MM 8 PCS
804571	STAINLESS STEEL ELECTRODES D. 2,5 MM 10 PCS
804572	STAINLESS STEEL ELECTRODES D. 3,2 MM 8 PCS
804564	RUTILE ELECTRODES D. 1,6 MM 15 PCS
804565	RUTILE ELECTRODES D. 2,0 MM 15 PCS
804566	RUTILE ELECTRODES D. 2,5 MM 15 PCS
804567	RUTILE ELECTRODES D. 3,2 MM 10 PCS
802620	RUTILE ELECTRODES D. 4 MM 8 PCS

BOXED ELECTRODES

802737	RUTILE ELECTRODES D. 2 MM 2,5 KG
802739	RUTILE ELECTRODES D. 2,5 MM 2,5 KG
802749	RUTILE ELECTRODES D. 3,2 MM 4 KG

ACCESSORIES/VARIOUS/SPARE PART

801096	MMA WELDING KIT 200A 16 MMQ 3+2M AX25
--------	---------------------------------------

DESCRIPTION

Inverter MMA electrode and TIG welding machine in direct current (DC) with scratch striking.
Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- robust, elevated construction against dust, water and dirt;
- display to show welding current;

- high welding current stability in spite of mains voltage fluctuations;
- arc force, hot start and anti-stick devices;
- thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.

Complete with MMA welding accessories and plastic carry case.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE

USEFUL LINKS



VIDEO