



- Battery manager for complete maintenance and rapid start of 12V/24V WET, GEL, AGM, MF, PbCa, EFB and Li batteries. 400A start max. With LCD screen.
- Automatic charge and maintenance in Pulse Tronic based on the technology of the selected battery.
- Battery test, start and alternator; regeneration and recovery of batteries; source of stable power supply for battery changes; starting.

TECHNICAL DATA

CODE	829343	CHARGE AND STARTING VOLTAG.	12 / 24 V	MIN.RATED REFERENCE CAPAC.	10 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFICIENT CHARGING CURRENT	90 A	MAX.RATED REFERENCE CAPAC.	1000 Ah
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	60 A	DIMENSIONS (LxWxH)	36,5 x 46 x 75,5 cm
CHARGING ABSORBED POWER	2 kW	START CUR.1V/C EN60335-2-29	300 A	WEIGHT	19,5 kg
STARTING ABSORBED POWER	12 kW	MAX STARTING CURRENT	400 A		

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES

802260 FUSES 80A 20 PCS

DESCRIPTION

Multifunction, electronic battery charger, starter and tester (BATTERY MANAGER), for WET, GEL, AGM, MF, PbCa, EFB and Li batteries at 12V/24V.

It grants complete maintenance of batteries and quick starting of cars, vans and light trucks.

It is an indispensable tool for stable power supply during battery changes.

Easy and intuitive to use thanks to the graphical LCD screen.

Features:

- Automatic charge and maintenance in Pulse Tronic;
- Battery, start and alternator test;
- Regeneration and recovery of batteries;
- Stable power source for battery changes (safeguard of the on-board electronics);
- Starting of all types of cars, vans, light trucks.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE