



- Battery charger and starter for 12/24V WET batteries and rapid cranking of all types of cars, vans, light goods vehicles. 300A max.
- Normal charge, fast (BOOST) charge, rapid cranking selection.
- Display of charging and cranking current.



- Protection against overcharging and pole inversion.

TECHNICAL DATA

CODE	829381	CHARGE AND STARTING VOLTAG.	12 / 24 V	MIN.RATED REFERENCE CAPAC.	20 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFICIENT CHARGING CURRENT	45 A	MAX.RATED REFERENCE CAPAC.	700 Ah
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	31 A	ADJUSTMENT POSITIONS	3
CHARGING ABSORBED POWER	1 kW	START CUR.1V/C EN60335-2-29	180 A	DIMENSIONS (LxWxH)	30,5 x 36 x 63 cm
STARTING ABSORBED POWER	6,4 kW	MAX STARTING CURRENT	300 A	WEIGHT	13,4 kg

SUPPLIED ACCESSORIES

712001	COLORADO 150B WORK CLAMP 150A
712002	COLORADO 150R POSITIVE CLAMP 150A
123425	CABLE 10 MMQ 2 M

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES

802259	FUSES 50A 20 PCS
--------	------------------

DESCRIPTION

Battery charger and starter for charging free electrolyte batteries (WET) with 12V/24V voltage and starting all kinds of cars, vans and light trucks.

Features:

- choice of normal charge, quick charge (BOOST), quick start;
- display of charging and starting current;
- protection against overloads and polarity reversal.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE