DYNAMIC 620 START





- Battery charger and starter for 12/24V WET batteries and rapid cranking of all types of cars, vans, light goods vehicles. 570A max.
- Normal charge, fast (BOOST) charge, rapid cranking selection.
- Display of charging and cranking current.

- Protection against overcharging and pole inversion.

TECHNICAL DATA

CODE	**829384**	CHARGE AND STARTING VOLTAG.	**12 / 24 V**	MIN.RATED REFERENCE CAPAC.	**20 Ah**
SINGLEPHASE MAINS VOLTAGE	**230 V**	EFFICIENT CHARGING CURRENT	**90 A**	MAX.RATED REFERENCE CAPAC.	**1550 Ah**
MAINS FREQUENCY	**50 / 60 Hz**	RATED CHAR.CUR.EN60335-2-29	**70 A**	ADJUSTMENT POSITIONS	**4**
CHARGING ABSORBED POWER	**2 kW**	START CUR.1V/C EN60335-2-29	**360 A**	DIMENSIONS (LxWxH)	**36,5 x 46 x 75,5 cm**
STARTING ABSORBED POWER	**10 kW**	MAX STARTING CURRENT	**570 A**	WEIGHT	**24 kg**

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES	
802029	FUSES 100A 20 PCS

DESCRIPTION

Battery charger and starter for charging free electrolyte batteries (WET) with 12V/24V voltage and starting all kinds of cars, vans and light trucks.
Features:

- choice of normal charge, quick charge (BOOST), quick start;
- timer for quick charge;
- display of charging and starting current;
- protection against overloads and polarity reversal.

DOWNLOAD

CATALOG IMAGE

INSTRUCTION MANUAL

CERTIFICATE