



INVERPULSE 425 CCC MIG/TIG/MMA 380V AQUA



基本信息

INVERPULSE 425 CCC MIG/TIG/MMA 380V AQUA
cod. 816522

技术参数

订货号 816522	交流最大输入电流 24 A	碳钢焊丝直径 (mm) 0,6 - 1,6 mm
电源 380 V	输入电流@60% (最大值A) 15,5 A	不锈钢焊丝直径 (mm) 0,8 - 1,6 mm
电源频率 50 / 60 Hz	输入功率 最大值KW 14 kW	铝焊丝直径 (mm) 0,8 - 1,6 mm
电流范围 10 - 400 A	输入功率@60% 8 kW	药芯焊丝直径 (mm) 1 - 1,6 mm
最大输出电流 350 A - 40 %	效率 (n%) 87 %	铜钎焊丝直径 (mm) 0,8 - 1,2 mm
额定电流@60% 300 A	功率因数 (cosphi) 0,8	防护等级 IP23
二次电压 83 V	直流使用的电极直径 (mm) 1,6 - 6 mm	

随附配件



INVERPULSE 425 CCC MIG/TIG/MMA 380V AQUA



ARGON GAS BOTTLE IT ADAPTOR - 432036



TROLLEY - UNIVERSAL - 803071



GAS REGULATOR 2 MANOMETERS - 722346



WATER COOLING UNIT GRA 3000 230V - 802497



MT500 MIG TORCH 3 M AQUA - 722625