



INVERPULSE 425 CCC MIG/TIG/MMA 380V AQUA



基本信息

INVERPULSE 425 CCC MIG/TIG/MMA 380V AQUA
cod. 816522

技术参数

CODE	订货号 816522	A_{MAX}	交流最大输入电流 24 A	ST	碳钢焊丝直径 (mm) 0,6 - 1,6 mm
V_{3PH}	电源 380 V	A_{MAX}^{60%}	输入电流@60% (最大值A) 15,5 A	SS	不锈钢焊丝直径 (mm) 0,8 - 1,6 mm
F	电源频率 50 / 60 Hz	P_{MAX}	输入功率 最大值KW 14 kW	AL	铝焊丝直径 (mm) 0,8 - 1,6 mm
A_{MIN}^{MAX}	电流范围 10 - 400 A	P_{60%}	输入功率@60% 8 kW	FX	药芯焊丝直径 (mm) 1 - 1,6 mm
A_{MAX}^{40°C}	最大输出电流 350 A - 40 %	η	效率 (n%) 87 %	BZ	铜钎焊丝直径 (mm) 0,8 - 1,2 mm
A_{60%}^{40°C}	额定电流@60% 300 A	φ	功率因数 (cosphi) 0,8	IP	防护等级 IP23
V₀	二次电压 83 V	φ_{DC}^{MIN/MAX}	直流使用的电极直径 (mm) 1,6 - 6 mm		

随附配件



INVERPULSE 425 CCC MIG/TIG/MMA 380V AQUA



ARGON GAS BOTTLE IT ADAPTOR - 432036



TROLLEY - UNIVERSAL - 803071



GAS REGULATOR 2 MANOMETERS - 722346



WATER COOLING UNIT GRA 3000 230V - 802497



MT500 MIG TORCH 3 M AQUA - 722625