





CODE	816151	MAX NO LOAD VOLTAGE IN DC	60 V	POWER FACTOR(cosphi) (cosphi)	0,7
SINGLEPHASE MAINS VOLTAGE	230 V	MAX ABSORBED CURRENT	38 A	D.USABLE ELECTRODES IN DC	1,6 - 4 mm
MAINS FREQUENCY	50 / 60 Hz	ABSORBED CURRENT AT 60%	22 A	INSULATION CLASS	F
CURRENT RANGE IN DC	5 - 200 A	MAX ABSORBED POWER	6 kW	PROTECTION DEGREE	IP23
MAX CURRENT DC EN60974-1	200 @ 35 % A	ABSORBED POWER AT 60%	3,3 kW	DIMENSIONS (LxWxH)	42 x 18,2 x 29,2 cm
CURRENT 35% DC	200 A	MOTORGENER. MINIMUM POWER	10 kW	WEIGHT	7,28 kg
DC CURRENT AT 60%	140 A	EFFICIENCY	89 %		



OTHER ACCESSORIES

803400 PLASTIC CARRY CASE - HEAVY DUTY

GAS REGULATORS

722346 GAS REGULATOR 2 MANOMETERS 32 L\min

TIG WELDING KITS

802491 TIG WELDING KIT - ST26V

TIG TORCHES

742058 ST26V 4M AX50 TIG TORCH

ACCESSORIES/VARIOUS/SPARE PART

801081 MMA WELDING KIT 300A 25 MMQ 4+3M AX50



MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Robust and impact resistant.

Features:

- compact and light;
- display to show welding current;
- Ø 50mm quick connector (socket);
- high welding current stability in spite of mains voltage fluctuations;
- arc force, hot start and anti-stick devices;
- thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.



TECHNOLOGY 236 XT



TECHNOLOGY 236 XT



TECHNOLOGY 236 XT